Rectangular pivot windows



A universal system

The system is designed for gap 4 windows but it has compensating shims in case of windows with increased gap dimensions.

A wide range of strikers make it compatible with all construction systems, both traditional and with continuous gasket.



	TOUR-30 layout 1 lath 30, axis 15		TOUR-30 layout 2 lath 30, axis 15		TOUR-35 layout 3 lath 35, axis 17,5		TOUR-35 layout 4 lath 35, axis 20		TOUR-40 layout 5 lath 40, axis 20	
	30-35-		35 55 55		35 35 77.5		47 20		45 22	
	Surface < 2 m ²	Surface > 2 m ²	Surface < 2 m²	Surface > 2 m ²	Surface < 2 m ²	Surface > 2 m ²	Surface < 2 m ²	Surface > 2 m ²	Surface < 2 m ²	Surface > 2 m ²
Upper strikers	×3	× 4	8 × 3	* × 4	×3	×4	* ×3	x 4	x 3	8 × 4
Lower strikers	×3	x 4	×3	× 4	x 3	x 4	× 3	× 4	×3	× 4
Limiting devices strikers	x 1	x 1	x 1	~	x 1	x1	x 1	x 1	x1	x1
		x 1		x 1		№ ×1) x 1		x1



Adjustment of the friction on the hinge

The hinge friction and the opening limiting device are easy to reach and adjust.

Friction hinges

Three models of friction hinges are available:

- with 30 mm rebate, 200 kg loading capacity
- with 35 mm rebate, 200 kg loading capacity
- with 40 mm rebate, 300 kg loading capacity.









More effective microventilation
The closing strikers leave complete freedom when choosing the handle and ensure a wider opening for really effective microventilation.



Easy cleaning
By unlocking the limiting striker with the wrench provided, the window rotates of 180° making the outside glass easier to clean.

